
OpenStack-Ansible Documentation: **os_tempest role** *Release 18.1.0.dev480*

OpenStack-Ansible Contributors

Dec 07, 2023

CONTENTS

- 1 Content: 3**
- 1.1 Overview 3
- 1.2 Team and repository tags 3
- 1.3 OpenStack-Ansible os_tempest role 3
 - 1.3.1 os_tempest mission 3
 - 1.3.2 Why? 4
 - 1.3.3 Advantages 4
- 1.4 User Guide 4
 - 1.4.1 Installation 4
 - 1.4.2 Usage 5
 - 1.4.3 Default variables 5
 - 1.4.4 os_tempest configuration 15

This is the Ansible role to deploy OpenStack Tempest.

tags

openstack, cloud, ansible, os_tempest

category

*nix

CONTENT:

1.1 Overview

1.2 Team and repository tags



1.3 OpenStack-Ansible os_tempest role

Ansible role to install OpenStack Tempest.

Documentation for the project can be found at:

https://docs.openstack.org/openstack-ansible-os_tempest/latest

Release notes for the project can be found at:

https://docs.openstack.org/releasenotes/openstack-ansible-os_tempest

The project source code repository is located at:

https://opendev.org/openstack/openstack-ansible-os_tempest

The project home is at:

<https://launchpad.net/openstack-ansible>

The project bug tracker is located at:

<https://bugs.launchpad.net/openstack-ansible>

Tempest is a testing framework consisting of a set of integration tests to test any deployed OpenStack cloud.

1.3.1 os_tempest mission

To provide a re-usable ansible role which installs, configures and runs Tempest.

1.3.2 Why?

The reason we have come up with this idea is because every OpenStack project uses playbooks and shell scripts to install, run and configure Tempest which are only slightly different but their purpose is the same.

When every project uses its own way to use Tempest, its really harder to cooperate (cross projects) together to solve any issues which may occur.

Thats where the re-usability steps in. By using the same role we can faster react to any issues which occurred in one project and may have an effect on another one.

1.3.3 Advantages

- maintenance of only one set of playbooks and scripts
- heads-up for issues related to particular tests
- bigger focus on development and maintenance of the one set of playbooks and scripts
- decreasing of time consumption needed to install, configure and run Tempest for new OpenStack projects - no need to write their CI Tempest procedures from scratch

1.4 User Guide

1.4.1 Installation

This page describes how to install os_tempest role.

To clone or view the source code of os_tempest, visit the role repository for [os_tempest](#).

Install dependencies via ansible-galaxy:

```
$ mkdir ~/.ansible/roles -p
$ git clone https://opendev.org/openstack/openstack-ansible-os_tempest ~/.
↪ansible/roles/os_tempest
$ ansible-galaxy install -r ~/.ansible/roles/os_tempest/requirements.yml --
↪roles-path ~/.ansible/roles/
```

Then you need to export a couple of variables, *ANSIBLE_ROLES_PATH* which points to the directory where os_tempest was cloned and *ANSIBLE_ACTION_PLUGINS* which points to the location of config_template plugin. In this case its:

```
$ export ANSIBLE_ROLES_PATH=$HOME/.ansible/roles
$ export ANSIBLE_ACTION_PLUGINS=~/.ansible/roles/config_template/action
```

Then create a `playbook.yaml`, you can find an [example one here](#). Then dont forget to set the name of the cloud youre going to run the role against, [see this page](#).

1.4.2 Usage

Execute by ansible-playbook

First you need to install `os_tempest` role. For more information about the installation process refer to the [Installation](#) page.

After the role is installed enter the `openstack-ansible-os_tempest` directory.

First thing which needs to be done in order to execute `os_tempest` role is setting a cloud name. For information on how to do that, please, have a look at [Set the name of the cloud](#) page.

An example `playbook.yml` can be seen below in [Example playbook](#) section.

After the required variables in the `playbook.yml` file are set you can execute the role as follows:

```
$ ansible-playbook playbook.yml
```

Example playbook

```
---
- name: Deploy Tempest
  hosts: localhost
  become: true
  vars:
    tempest_cloud_name: mycloud
    tempest_run: true
  roles:
    - os_tempest
```

Dependencies

This role requires the following packages to be installed on the target host:

- pip >= 7.1
- python-virtualenv

1.4.3 Default variables

```
## Verbosity Options
debug: False

stestr_executable: "{{ _stestr_executable | default('stestr') }}"

# Install openstack tempest
# set the tempest_install_method to source or distro
# on choosing source it will install from git or venv
# on choosing distro it will install based on distribution
tempest_install_method: "{{ service_install_method | default('source') }}"
```

(continues on next page)

(continued from previous page)

```
tempest_venv_python_executable: "{{ openstack_venv_python_executable | default(_tempest_venv_python_executable) | default('python3') }}"

# Set the package install state for distribution and pip packages
# # Options are 'present' and 'latest'
tempest_package_state: "latest"

# Set the host which will execute the shade modules
# for the service setup. The host must already have
# clouds.yaml properly configured.
tempest_service_setup_host: "{{ openstack_service_setup_host | default('localhost') }}"
tempest_service_setup_host_python_interpreter: >-
  {{
    openstack_service_setup_host_python_interpreter | default(
      (tempest_service_setup_host == 'localhost') | ternary(ansible_playbook_
        python, ansible_facts['python']['executable']))
  }}

# Toggle whether tempest actually executes
tempest_run: no
# Toggle whether tempest cleanup executes prior and after regular tempest run
tempest_cleanup: no
# if tempest_cleanup_dry_run is set to true, tempest cleanup will log all
  found
# leftover resources to a dry_run.json file, none resources will be deleted
# tempest_cleanup_dry_run: no

# Credential Provider Mechanisms
# If tempest_test_accounts is not an empty string, then use_dynamic_
  credentials will be turned off
tempest_test_accounts: ""
tempest_test_accounts_file_path: "{{ tempest_workspace }}/etc/tempest_
  accounts.yaml"
# tempest_create_isolated_networks has an effect only when use_dynamic_
  credentials is enabled
tempest_create_isolated_networks: true
# tempest_fixed_network_name does not have an effect when dynamic credentials_
  are used together with tempest_create_isolated_networks
tempest_fixed_network_name: public

# Tempest Resources
# Toggle whether default resources are implemented
tempest_default_role_resources: yes
tempest_public_net_create: true
tempest_private_net_create: false
tempest_router_create: false
tempest_images_create: true
tempest_flavors_create: true
```

(continues on next page)

(continued from previous page)

```

tempest_projects_create: "{{ tempest_public_net_create or tempest_private_net_
↳create or tempest_router_create }}"

# Define 0 (serial) or more to use a non default concurrency
# tempest_run_concurrency:

# Define the worker file to be used by tempest
# This worker file is parsed to stestr to manually schedule tempest tests
# tempest_test_worker_file_path:

# We comment `tempest_git_repo` so that we do not attempt to build the wheel_
↳from this repo/branch.
# Instead, we want tempest to get built from the stable release defined in_
↳global requirements.
# tempest_git_repo: https://opendev.org/openstack/tempest
tempest_git_install_branch: master
tempest_upper_constraints_url: >-
  {{ requirements_git_url | default('https://releases.openstack.org/
↳constraints/upper/' ~ requirements_git_install_branch | default('master')) }
↳}
tempest_git_constraints:
  - "--constraint {{ tempest_upper_constraints_url }}"

tempest_pip_install_args: "{{ pip_install_options | default('') }}"

# Name of the virtual env to deploy into
tempest_venv_tag: "{{ venv_tag | default('untagged') }}"
tempest_venv_bin: "/openstack/venvs/tempest-{{ tempest_venv_tag }}/bin"

# The location where the tempest logs will be placed
tempest_log_dir: "/var/log/tempest"

## Tempest Plugins
# Extra plugins can be defined in ``tempest_extra_plugins``.
# tempest_extra_plugins:
#   - name: custom-tempest-plugin
#     repo: https://opendev.org/openstack/custom-tempest-plugin
#     branch: master
#     install: true
tempest_extra_plugins: []
tempest_plugins: "{{ (_tempest_plugins + tempest_extra_plugins) | selectattr(
↳'install', 'equalto', true) }}"

tempest_plugin_barbican_git_repo: https://opendev.org/openstack/barbican-
↳tempest-plugin
tempest_plugin_barbican_git_install_branch: master

tempest_plugin_cinder_git_repo: https://opendev.org/openstack/cinder-tempest-
↳plugin

```

(continues on next page)

(continued from previous page)

```
tempest_plugin_cinder_git_install_branch: master

tempest_plugin_cloudkitty_git_repo: https://opendev.org/openstack/cloudkitty-
↳tempest-plugin
tempest_plugin_cloudkitty_git_install_branch: master

tempest_plugin_designate_git_repo: https://opendev.org/openstack/designate-
↳tempest-plugin
tempest_plugin_designate_git_install_branch: master

tempest_plugin_glance_git_repo: https://opendev.org/openstack/glance-tempest-
↳plugin
tempest_plugin_glance_git_install_branch: master

tempest_plugin_heat_git_repo: https://opendev.org/openstack/heat-tempest-
↳plugin
tempest_plugin_heat_git_install_branch: master

tempest_plugin_ironic_git_repo: https://opendev.org/openstack/ironic-tempest-
↳plugin
tempest_plugin_ironic_git_install_branch: master

tempest_plugin_keystone_git_repo: https://opendev.org/openstack/keystone-
↳tempest-plugin
tempest_plugin_keystone_git_install_branch: master

tempest_plugin_magnum_git_repo: https://opendev.org/openstack/magnum-tempest-
↳plugin
tempest_plugin_magnum_git_install_branch: master

tempest_plugin_manila_git_repo: https://opendev.org/openstack/manila-tempest-
↳plugin
tempest_plugin_manila_git_install_branch: master

tempest_plugin_murano_git_repo: https://opendev.org/openstack/murano-tempest-
↳plugin
tempest_plugin_murano_git_install_branch: master

tempest_plugin_neutron_git_repo: https://opendev.org/openstack/neutron-
↳tempest-plugin
tempest_plugin_neutron_git_install_branch: master

tempest_plugin_novajoin_git_repo: https://opendev.org/x/novajoin-tempest-
↳plugin
tempest_plugin_novajoin_git_install_branch: master

tempest_plugin_octavia_git_repo: https://opendev.org/openstack/octavia-
↳tempest-plugin
tempest_plugin_octavia_git_install_branch: master
```

(continues on next page)

(continued from previous page)

```
tempest_plugin_senlin_git_repo: https://opendev.org/openstack/senlin-tempest-
↳plugin
tempest_plugin_senlin_git_install_branch: master

tempest_plugin_sahara_git_repo: https://opendev.org/openstack/sahara-tests
tempest_plugin_sahara_git_install_branch: master

tempest_plugin_telemetry_git_repo: https://opendev.org/openstack/telemetry-
↳tempest-plugin
tempest_plugin_telemetry_git_install_branch: master

tempest_plugin_trove_git_repo: https://opendev.org/openstack/trove-tempest-
↳plugin
tempest_plugin_trove_git_install_branch: master

tempest_plugin_zaqar_git_repo: https://opendev.org/openstack/zaqar-tempest-
↳plugin
tempest_plugin_zaqar_git_install_branch: master

tempest_plugin_zun_git_repo: https://opendev.org/openstack/zun-tempest-plugin
tempest_plugin_zun_git_install_branch: master

# tempest_workspace where tempest can be runned
tempest_workspace: "{{ ansible_facts['env']['HOME'] }}/workspace"

# The location where the test include/exclude lists will be placed
tempest_includelist_file_path: "{{ tempest_workspace }}/etc/tempest_
↳includelist.txt"
tempest_excludelist_file_path: "{{ tempest_workspace }}/etc/tempest_
↳excludelist.txt"

# Variable prefixes that will be dynamically gathered to create the include/
↳exclude list
tempest_test_search_includelist_pattern: 'tempest_test_includelist_'
tempest_test_search_excludelist_pattern: 'tempest_test_excludelist_'

# Tests to execute:
# This sets up a list of tests to execute based on what's deployed in the_
↳environment.
# The list gets added to the includelist which tempest executes.
tempest_test_includelist: []

# Extra test to be executed
tempest_test_extra_test: []

# Tests being skipped by os_tempest
# Example:
# tempest_test_excludelist:
```

(continues on next page)

(continued from previous page)

```
# - test: tempest.scenario.test.minimum_basic
#   reason: This test is failing
#   lp: 'https://bugs.launchpad.net/openstack-ansible/+bug/123456'
#   bz: 'https://bugzilla.redhat.com/show_bug.cgi?id=123456'
# OR
# tempest_test_excludelist:
#   - 'tempest.scenario.test.minimum_basic'
tempest_test_excludelist: []

# Private network configuration
# Currently supports 2 types
# vlan - will need to make sure your seg id and subnet cidr are correct
# vxlan - default, can change subnet cidr and seg id

tempest_private_net_name: "private"
tempest_private_subnet_name: "private-subnet"
tempest_private_subnet_cidr: "192.168.74.0/28"
tempest_private_net_provider_type: "vxlan"
tempest_private_net_seg_id:
# If you choose vlan as private network provider type, you must set a physical
# name for it
# tempest_private_net_physical_name: "private"

# Public network configuration
# Currently supports 2 types
# Flat - default
# Vlan - make sure you override seg id, cidr, provider and physical
tempest_public_net_name: "public"
tempest_public_subnet_name: "public-subnet"
tempest_public_subnet_cidr: "10.1.13.0/24"
# Neutron default gateway to first ip of subnet, usually .1
# tempest_public_subnet_gateway_ip:
tempest_public_net_provider_type: "flat"
# TODO(chkumar246):
# The use of _type is to provide backwards compatibility for
# overrides in S and can be removed in T.
tempest_public_net_physical_name: "{{ tempest_public_net_physical_type |
↪default('flat') }}"
tempest_public_net_seg_id: ""
tempest_public_router_external: "True"
# Example allocation range:
# tempest_public_subnet_allocation_pools: "10.1.13.150-10.1.13.200"
tempest_public_subnet_allocation_pools: ""

tempest_compute_image_ssh_user: cirros
tempest_compute_run_ssh: True
tempest_network_ping_gateway: False

tempest_dashboard_url: "https://{{ external_lb_vip_address | default('127.0.0.
```

(continues on next page)

(continued from previous page)

```

↪1') }}/"

# var for setting tempest_service_available_{service_name} vars
# Example:
# tempest_services:
#   - cinder
#   - aodh
# It will set tempest_service_available_aodh and
# tempest_service_available_cinder to true.
tempest_services: []

tempest_service_available_aodh: "{{ groups['aodh_all'] is defined and groups[
↪'aodh_all'] | length > 0 }}"
tempest_service_available_barbican: "{{ groups['barbican_all'] is defined and
↪groups['barbican_all'] | length > 0 }}"
tempest_service_available_ceilometer: "{{ groups['ceilometer_all'] is defined
↪and groups['ceilometer_all'] | length > 0 }}"
tempest_service_available_cinder: "{{ groups['cinder_all'] is defined and
↪groups['cinder_all'] | length > 0 }}"
tempest_service_available_cloudkitty: "{{ groups['cloudkitty_all'] is defined
↪and groups['cloudkitty_all'] | length > 0 }}"
tempest_service_available_designate: "{{ groups['designate_all'] is defined
↪and groups['designate_all'] | length > 0 }}"
tempest_service_available_glance: "{{ groups['glance_all'] is defined and
↪groups['glance_all'] | length > 0 }}"
tempest_service_available_gnocchi: "{{ groups['gnocchi_all'] is defined and
↪groups['gnocchi_all'] | length > 0 }}"
tempest_service_available_heat: "{{ groups['heat_all'] is defined and groups[
↪'heat_all'] | length > 0 }}"
tempest_service_available_horizon: "{{ groups['horizon_all'] is defined and
↪groups['horizon_all'] | length > 0 }}"
tempest_service_available_ironic: "{{ groups['ironic_all'] is defined and
↪groups['ironic_all'] | length > 0 }}"
tempest_service_available_magnum: "{{ groups['magnum_all'] is defined and
↪groups['magnum_all'] | length > 0 }}"
tempest_service_available_manila: "{{ groups['manila_all'] is defined and
↪groups['manila_all'] | length > 0 }}"
tempest_service_available_mistral: "{{ groups['mistral_all'] is defined and
↪groups['mistral_all'] | length > 0 }}"
tempest_service_available_murano: "{{ groups['murano_all'] is defined and
↪groups['murano_all'] | length > 0 }}"
tempest_service_available_neutron: "{{ groups['neutron_all'] is defined and
↪groups['neutron_all'] | length > 0 }}"
tempest_service_available_neutron_bgpvpn: >-
    {{ (groups['neutron_all'] is defined) and (groups['neutron_all'] | length >
↪0) and ('bgpvpn' in neutron_plugin_base | default([])) }}
tempest_service_available_neutron_vpnaas: >-
    {{ (groups['neutron_all'] is defined) and (groups['neutron_all'] | length >
↪0) and ('vpnaas' in neutron_plugin_base | default([])) }}

```

(continues on next page)

(continued from previous page)

```

tempest_service_available_nova: "{{ groups['nova_all'] is defined and groups[
↳'nova_all'] | length > 0 }}"
tempest_service_available_novajoin: False
tempest_service_available_octavia: "{{ groups['octavia_all'] is defined and
↳groups['octavia_all'] | length > 0 }}"
tempest_service_available_sahara: "{{ groups['sahara_all'] is defined and
↳groups['sahara_all'] | length > 0 }}"
tempest_service_available_senlin: "{{ groups['senlin_all'] is defined and
↳groups['senlin_all'] | length > 0 }}"
tempest_service_available_swift: >-
  {{
    (groups['swift_all'] is defined and groups['swift_all'] | length > 0) or
    (groups['ceph-rgw'] is defined and groups['ceph-rgw'] | length > 0) or
    (ceph_rgws is defined and ceph_rgws | length > 0)
  }}
tempest_service_available_trove: "{{ groups['trove_all'] is defined and
↳groups['trove_all'] | length > 0 }}"
tempest_service_available_whitebox: False
tempest_service_available_whitebox_neutron: False
tempest_service_available_zaqar: "{{ groups['zaqar_all'] is defined and
↳groups['zaqar_all'] | length > 0 }}"
tempest_service_available_zun: "{{ groups['zun_all'] is defined and groups[
↳'zun_all'] | length > 0 }}"

# Var for setting ssl verification
tempest_keystone_interface_insecure: "{{ (keystone_service_internaluri_
↳insecure | default(false)) | bool }}"

tempest_pip_packages:
- "{{
  (tempest_git_repo is defined) | ternary(
    'git+' ~ (tempest_git_repo | default('https://opendev.org/openstack/
↳tempest.git')) ~ '@' ~ tempest_git_install_branch ~ '#egg=tempest',
    'tempest')
  }}"
- cmd2
- ddt
- junitxml
- lxml
- nose
- python-cinderclient
- python-glanceclient
- python-heatclient
- python-keystoneclient
- python-manilaclient
- python-memcached
- python-neutronclient
- python-novaclient
- python-openstackclient

```

(continues on next page)

(continued from previous page)

```

- python-senlinclient
- python-saharaclient
- python-subunit
- python-swiftclient
- python-troveclient
- testscenarios
- os-testr

# The list of images for tempest to download for the current architecture, as
↳defined
# in this role vars/main.yml file
# To override this list, use a list of the form
# tempest_images:
#   - url: ...           where to download from (required)
#     checksum: ...      checksum to validate downloaded file, format:
↳<algorithm><checksum> (optional)
#     format: ...        format to use when uploading to glance (required)
#     name: ...          name to use when uploading to glance (optional)
#     properties:        a dict of custom properties to attach to the image in
↳glance (optional)
#       <property>: <value>
tempest_images: "{{ tempest_images_map[ansible_facts['architecture']] }}"

# The location where images are downloaded to
tempest_image_dir: "{{ lookup('env', 'HOME') }}/tempest-images"

tempest_flavors:
- name: tempest1
  id: 201
  ram: 256
  disk: 1
  vcpus: 1
- name: tempest2
  id: 202
  ram: 512
  disk: 1
  vcpus: 1

# The projects for tempest to use
tempest_projects:
- "tempest"

## Tunable overrides
tempest_tempest_conf_search_overrides_pattern: 'tempest_tempest_conf_overrides
↳'
tempest_tempest_conf_overrides: {}

## The name of cloud from clouds.yaml
tempest_cloud_name: "default"

```

(continues on next page)

(continued from previous page)

```

## The name of domain from clouds.yaml
tempest_domain_name: "Default"

## The name of interface from clouds.yaml
tempest_interface_name: "internal"

# The default endpoint type to use by tempest
tempest_endpoint_type: "internal"

# python-tempestconf variables
# The tempest_use_tempestconf by default is set to false, set to true if you
# want to generate the tempest.conf file with this tool, instead of
# tempest.conf from the template
tempest_use_tempestconf: false
tempest_tempestconf_venv_tag: "{{ venv_tag | default('untagged') }}"
tempest_tempestconf_venv_bin: "/openstack/venvs/tempestconf-{{ tempest_
↳tempestconf_venv_tag }}/bin"

# We comment out `tempest_tempestconf_git_repo` so that the repo_build role
↳does not attempt to
# build the wheel from this repo/branch. Instead, we want python-tempestconf
↳to get built
# from the stable release defined in global requirements.
# tempest_tempestconf_git_repo: https://opendev.org/openinfra/python-
↳tempestconf
tempest_tempestconf_git_install_branch: master
tempest_tempestconf_git_constraints:
  - "--constraint {{ tempest_upper_constraints_url }}"
tempest_tempestconf_pip_packages:
  - "{{
    (tempest_tempestconf_git_repo is defined) | ternary(
      'git+' ~ (tempest_tempestconf_git_repo | default(
        'https://opendev.org/openinfra/python-tempestconf')
      ) ~ '@' ~ tempest_tempestconf_git_install_branch ~ '#egg=python_
↳tempestconf',
      'python_tempestconf')
    }}"
tempest_tempestconf_profile:
  debug: true
  create: true
  os-cloud: "{{ tempest_cloud_name }}"
  out: "{{ tempest_workspace }}/etc/tempest.conf"
  network-id: "{{ tempest_neutron_public_network_id }}"
  overrides: "{{ tempest_tempestconf_profile_overrides }}"
tempest_tempestconf_profile_extras: {}
tempest_tempestconf_profile_overrides: "{{ tempest_tempest_conf_overrides }}"

# Stackviz tarball url

```

(continues on next page)

(continued from previous page)

```
stackviz_pip_install_args: "{{ pip_install_options | default('--isolated') }}"
stackviz_tarball: "https://tarballs.opendev.org/openstack/stackviz/dist/
↳stackviz-latest.tar.gz"
stackviz_venv_tag: "{{ venv_tag | default('untagged') }}"
stackviz_venv_bin: "/openstack/venvs/stackviz-{{ stackviz_venv_tag }}/bin"
tempest_run_stackviz: true
```

1.4.4 os_tempest configuration

This page shows all of the variables which can be set in order to control the behaviour of os_tempest role and provides examples on how to do so.

For a list of all variables with a default value set, please, refer to the [this page](#).

Set the name of the cloud

os-tempest uses named cloud credentials so it requires the name of the cloud the role will be executed against. The name is provided to os-tempest via the tempest_cloud_name variable. In order to use named clouds a clouds.yaml file needs to be present on the **target host**. clouds.yaml file needs to be stored at one of the supported locations, [see here](#) For more information about named clouds, please, follow to the [os-client-config official documentation](#)

Warning: clouds.yaml file has to be present on the target host - the host os_tempest is gonna be executed against.

Resource creation

Tempest requires some openstack resources(like flavors and images) in order to function properly. It is possible to choose which resources should be created or to skip resource creation at all. Below example shows how to use already existing public network and images.

```
tempest_default_role_resources: true
tempest_public_net_create: false
tempest_neutron_public_network_id: <network_id>
tempest_images_create: false
tempest_glance_image_id_1: <image_id>
tempest_glance_image_id_2: <image_id>
```

python-tempestconf

python-tempestconf is a tool which generates a `tempest.conf` file necessary for Tempest execution. For more information about the tool, please, [follow its official documentation](#).

If you want `os_tempest` to execute `python-tempestconf`, prior to Tempest execution in order to generate `tempest.conf` file, set `tempest_use_tempestconf` variable to true:

```
tempest_use_tempestconf: true
```

More information about `python-tempestconf` arguments can [be found here](#).

The best way how to pass any arguments to `python-tempestconf` is using its [profile feature](#).

`os_tempest` provides `tempest_tempestconf_profile` variable for setting desired `python-tempestconf`s arguments. For example, if you wanted to define **debug** to `true`, **os-cloud** to `demo` and override output of `python-tempestconf` to `/my/location/tempest.conf`, it would be done by:

```
tempest_tempestconf_profile:  
  debug: true  
  os-cloud: demo  
  out: /my/location/tempest.conf
```

- [search](#)